

Hoses

110 CL Heavy Duty Suction and Discharge Hose



- Temperature Ranges: -13°F to 140°F
- Applications: Heavy duty water suction and discharge hose for use in industrial, construction, and agricultural applications.
- Construction: Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.
- Available by the foot or 100 ft. rolls

How to Order:

K-110 3/4C (3/4" hose)
K-110 1C (1" hose)

110 GR Heavy Duty Suction and Discharge Hose



- Temperature Range: -13°F to 140°F
- Applications: Heavy duty water suction and discharge hose for use in industrial, construction, and agricultural applications.
- Construction: Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.
- Available by the foot or 100 ft. rolls

How to Order:

K-110 3/4G (3/4" hose)
K-110 1G (1" hose)

112 CL Economical Heavy Duty Suction and Discharge Hose



- Temperature Range: -13°F to 140°F
- Applications: Economical heavy duty water suction and discharge hose for use in industrial, construction, and agricultural applications.
- Construction: Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.
- Available by the foot or 100 ft. rolls

How to Order:

K-112 1-1/4C (1-1/4" hose)
K-112 1-1/2C (1-1/2" hose)
K-112 2C (2" hose)
K-112 2-1/2C (2-1/2" hose)
K-112 3C (3" hose)
K-112 4C (4" hose)

112 GR Economical Heavy Duty Suction & Discharge Hose 1-1/2"



- Temperature Range: -13°F to 140°F
- Application: Economical heavy duty water suction hose for use in industrial, agriculture, and construction applications.
- Construction: Flexible PVC, rigid PVC helix, smooth bore, smooth O.D.
- Available by the foot or 100 ft. rolls

How to Order:

K-112 1-1/4G (1-1/4" hose)
K-112 1-1/2G (1-1/2" hose)
K-112 2G (2" hose)
K-112 2-1/2G (2-1/2" hose)
K-112 3G (3" hose)
K-112 4G (4" hose)

Hoses

130 Oil Resistant PVC Suction and Discharge Hose



- Temperature Range: -13°F to 140°F
- Applications: Oil resistant heavy duty suction and transfer hose for use with light oils and animal fats.
- Construction: Flexible oil-resistant PVC, rigid PVC helix, smooth bore, smooth O.D.
- Available in rolls of 100 ft. only

How to Order:

K-130 1-1/2 (1-1/2" hose)
 K-130 2 (2" hose)
 K-130 3 (3" hose)

390SD All Weather Suction and Discharge Hose



- Temperature Range: -40°F to 140°F
- Applications: All weather suction and discharge hose of liquids in the construction, rental, and agricultural industries.
- Construction: EPDM rubber, polyethylene helix, synthetic braiding, smooth bore, corrugated O.D.
- Available by the foot or 100 ft. rolls

How to Order:

K-390 1-1/4 (1-1/4" hose)
 K-390 1-1/2 (1-1/2" hose)
 K-390 2 (2" hose)
 K-390 3 (3" hose)

620WD General Ducting and Blower Hose with Wire Helix



- Temperature Range: -40°F to 220°F
- Applications: General ducting and Blower applications for use with lightweight abrasives such as saw dust, fumes, dust, grass clippings, street refuse, and cotton pickers.
- Construction: EPDM rubber, metal wire helix, smooth bore, slightly corrugated O.D.
- Available by the foot or 50 ft. sections

How to Order:

K-620WD 2-1/2 (2-1/2" hose)
 K-620WD 3 (3" hose)
 K-620WD 4 (4" hose)
 K-620WD 6 (6" hose)
 K-620WD 8 (8" hose)
 K-620WD 5 (5" hose)
 K-620WD 10 (10" hose)
 K-620WD 12 (12" hose)

Hoses



High Pressure Polyethylene Rubber Blend Reinforced Chemical Spray & Transfer Hose




- Temperature Range: -40 to 130 °F
- Applications: High pressure orchard and vineyard spraying, chemical transfer.
- Construction: Tube - Co-extruded blue LLDPE/rubber blend with high tensile strength yarn reinforcement, blue rubber blend compound cover. Silicone free.
- Maximum working pressure: 800 PSI (for 3/8"-3/4") 400 PSI (for 1")
- Available by the foot or in 100 ft. rolls.

How to Order:

A4086-06	(3/8" hose)
A4086-08	(1/2" hose)
A4086-12	(3/4" hose)
A4086-16	(1" hose)

Lay Flat Blue PVC Discharge Hose



- Temperature Range: -5 to 170 °F
- Applications: PVC hose used for general open end water discharge.
- Construction: Polyester yarn spiral wrap, longitudinal strength member and homogeneous PVC tube and cover to prevent separation.
- Available by the foot or in 300 ft. rolls.

How to Order:

BL-160 1-1/2	(1-1/2" hose)
BL-160 2	(2" hose)
BL-160 3	(3" hose)
BL-160 4	(4" hose)

Linear Low Density Polyethylene Tubing



- Applications: Transfer of air and liquids, resistant to solvents, chemically inert.
- Construction: Linear low density polyethylene tubing- natural color, lightweight.
- Available in 100 ft. rolls only.

How to Order:

FUM 1/4	(1/4" tubing)
FUM 3/8	(3/8" tubing)
FUM 1/2	(1/2" tubing)
FUM 3/4	(3/4" tubing)



BW "Blue Water" Low Temperature PVC Suction Hose



- Temperature Range: -40°F to 150°F
- General Applications: Extreme cold conditions, pumps, rental and construction dewatering, water suction - standard duty
- Construction: PVC tube
- Available in 100 ft. rolls only.

How to Order:

BW150 1-1/2	(1-1/2" hose)
BW200 2	(2" hose)

Hoses



All Purpose EPDM Rubber Hose



- Temperature Range: -40 to +200 °F
- Applications: Widespread use in industrial, agricultural, construction, and marine applications. Use also as a hot or cold water washdown, heavy-duty heater, or low pressure agricultural spray hose.
- Construction: Cover is red or black abrasion and ozone-resistant EPDM with spiral polyester yarn reinforcement. Silicone free core and cover.
- Available by the foot or in reels of 300 ft. for 1-1/4", 250 ft. for 1-1/2" or 200 ft. for 2"
- Maximum pressure 200 P.S.I., 4 spiral.

How to Order:

L-81-R 1-1/4	(1-1/4" red hose)
L-81-R 1-1/2	(1-1/2" red hose)
L-81-R 2	(2" red hose)

All Purpose EPDM Rubber Hose



- Temperature Range: -40°F to 180°F
- Applications: for liquid spray units, from hand-held units to large floater spray units handling liquid fertilizer solutions.
- Reinforcement: multiple high tensile textile spiral.
- Cover: red chemical, weather and ozone resistant EDPM.
- Available by the foot or in reels of 700 ft.
- Maximum pressure 150 P.S.I., 2 spiral.

How to Order:

L-85-R 3/8	(3/8" red hose)
L-85-R 1/2	(1/2" red hose)
L-85-R 3/4	(3/4" red hose)
L-85-R 1	(1" red hose)

Chemical Transfer Hose




- Temperature Range: -40°F – 180°F
- Applications: For chemical transfer of solvents and chemicals for in-plant or tank truck use. Handles almost every common chemical in the chemical industry.
- Construction: Clear UHMWP (ultra-high molecular weight polyethylene)
- Reinforcement: Multiple high tensile textile braids with dual wire helix.
- Cover: green with white and orange stripe chemical, weather and ozone resistant EPDM.
- Available by the foot.

How to Order:

N-2700 3/4	(3/4" hose)
N-2700 1	(1" hose)
N-2700 1-1/4	(1-1/4" hose)
N-2700 1-1/2	(1-1/2" hose)
N-2700 2	(2" hose)
N-2700 3	(3" hose)
N-2700 4	(4" hose)

Hoses

Clear Braided Vinyl Tubing




- Temperature Range - 25°F to 150°F
- Applications - Excellent for handguns and other sprayer applications.
- Construction - High grade polyvinyl chloride
- Available by the foot or in 100 ft. rolls.

How to Order:

A-87 1/4	(1/4" tubing)
A-87 3/8	(3/8" tubing)
A-87 1/2	(1/2" tubing)
A-87 5/8	(5/8" tubing)
A-87 3/4	(3/4" tubing)
A-87 1	(1" tubing)

Clear Vinyl Tubing



- Temperature Range - 5°F to 150°F
- Application - Use on air compressor lines, blower lines, water circulation
- Construction - High grade polyvinyl chloride.
- Available by the foot or in 100 ft. rolls.

How to Order: (1/16" Wall)

V-1155 1/4	(1/4" thin tube 1/16" wall)
V-1155 3/8	(3/8" thin tube 1/16" wall)
V-1155 1/2	(1/2" thin tube 1-16" wall)

How to Order: (1/8" Wall)

V-1155-H 1/4	(1/4" thick tube 1/8" wall)
V-1155-H 3/8	(3/8" thick tube 1/8" wall)
V-1155-H 1/2	(1/2" thick tube 1/8" wall)
V-1155-H 5/8	(5/8" thick tube 1/8" wall)
V-1155-H 3/4	(3/4" thick tube 1/8" wall)
V-1155 H 1	(1" thick tube 1/8" wall)

V137 High Pressure AG Spray Hose



For transfer of liquid solutions for the agriculture industry.

- Temperature Range: Ambient
- Applications – Spray hose used for spray applications with water-soluble chemicals.
- Construction - White PVC tubing with weather and ozone resistant PVC.
- Available by the foot or in 300 ft. rolls.

How to Order:

V-137 3/8	(3/8" hose)
V-137 1/2	(1/2" hose)
V-137 3/4	(3/4" hose)



V-300 Multi-Purpose Air, Water and Spray Hose



- Temperature Range: -15 to 150 °F
- Applications: Transfer of air, water and mild water-soluble chemicals. Outdoor applications requiring a low temp hose.
- Construction -Tube - Black PVC compound.
- Reinforcement - Spiral polyester yarn with additional longitudinal yarns
- Cover - yellow PVC compound
- Maximum pressure 300 P.S.I.
- * Available by the foot or in 100 or 300 ft. rolls

How to Order:

V-300 3/8	(3/8" hose)
V-300 1/2	(1/2" hose)
V-300 3/4	(3/4" hose)
V-300 1	(1" hose)

Hoses



Mill Discharge Double Jacket Contractor Grade Discharge Hose



Double jacket contractor grade assemblies with male and female aluminum rocker lug couplings. Hose is constructed with 100% polyester yarn and a cover that will not rot even if the hose is stored wet. Not intended for use as a fire hose.

- Temperature Range: 25° F (-31° C) to 185° F (+85° C)
- Applications: Municipal washdown, Hydrant to truck water supply lines, Heavy duty equipment pump rental, Ship deck washdown
- Construction: Double jacket with 100% polyester yarn.
- Water and mildew-resistant cover, will not rot, even when stored wet.
- Smooth natural rubber tube - Provides strength and flexibility.
- Double Jacket - Provides greater abrasion resistance.

How to Order (Order in Lengths):

DJ150NSTX50 (1-1/2" hose) 50' Length
DJ250NSTX50 (2-1/2" hose) 50' Length

NH3 Hoses



N2000 Anhydrous Ammonia Hose (NH3)



- Temperature Range: -40°F to 180°F
- High grade low permeation EPDM
- Reinforcement: Multiple high tensile Nylon braids
- Cover: black chemical, weather and ozone resistant EPDM w/green longitudinal stripe.
- Recommended fittings swaged male pipe thread, interlocking clamp type

Sold only in coupled assemblies - Please specify length

How to Order (Order in Lengths):

N-2000 3/4 (3/4" hose) Specify Length
N-2000 1 (1" hose) Specify Length
N-2000 1-1/4 (1-1/4" hose) Specify Length
N-2000 2 (2" hose) Specify Length

**6 yr. Manufacturer's
Warranty**

**Each hose comes
with a Hydrostatic
Test Certificate**

V1150 EVA Applicator Tubing



For transfer of liquid solutions for the agriculture industry.

- Temperature Range: – softening point at 148°F
- Applications: EVA tubing for anhydrous ammonia (NH3)
- Construction: Ozone resistant blue tinted EVA copolymer
- Available by the foot or in 250 ft. rolls of 3/8", 300 ft. of 1/2" or 200 ft. of 3/4" hose.

How to Order (By the Roll):

V-1550 3/8 (250' Roll)
V-1150 1/2 (300' Roll)
V-1150 3/4 (200' Roll)

Hose Clamps and Hose Cutters

Banjo Super Clamps



Features:

- Stainless steel construction.
- Stainless steel bolt with silver plated nut to prevent seizing.
- 3 spot welds for extra strength.
- Ideal for high torque applications.
- Nylon lock nut feature.
- 360° sealing surface.
- T-bolt design.
- Available individually or in bags of 10



PART #	CLAMP SIZE	FITS HOSE MIN/MAX
T-BOLT HOSE CLAMP		
TC120	1"	1.20"/1.34"
TC130	1-1/4"	1.30"/1.70"
TC150	1-1/2"	1.50"/1.75"
TC162	1-1/4"	1.62"/1.87"
TC181	1-1/2"	1.81"/2.06"
TC193	1-1/2"	1.93"/2.18"
TC206	2"	2.06"/2.40"
TC218	2"	2.18"/2.50"
TC224	2"	2.24"/2.55"
TC231	2"	2.31"/2.62"
TC250	2"	2.50"/2.81"
TC287	2"	2.87"/3.18"
TC312	3"	3.12"/3.49"
TC331	3"	3.31"/3.62"
TC343	3"	3.43"/3.75"
TC425	4"	4.25"/4.56"
TC438	4"	4.38"/4.76"
TC456	4"	4.56"/4.94"

Worm Gear Clamps

All stainless construction 5/16" Hexagon and Screw-driver Slotted Screw

Features:

- Marine Grade SAE 300 series stainless band and housing with SAE 305 series stainless screw.
- Upgraded to four piece construction
- Available individually or in boxes of 10



PART #	CLAMP SIZE	FITS HOSE MIN/MAX
WORM GEAR CLAMPS		
HSS6	1/2"	28/64" - 50/64"
HSS8	1/2"	32/64" - 58/64"
HSS10	1/2"	36/64" - 1-4/64"
HSS12	1/2"	52/64" - 1-32/64"
HSS16	1/2"	52/64" - 1-48/64"
HSS20	1/2"	1-4/64" - 2"
HSS24	1/2"	1-20/64" - 2-16/64"
HSS28	1/2"	1-36/64" - 2-32/64"
HSS32	1/2"	1-52/64" - 2-48/64"
HSS36	1/2"	2-4/64" - 3"
HSS40	1/2"	36/64" - 1-48/64"
HSS44	1/2"	2-20/64" - 3-16/64"
HSS48	1/2"	20-36/64" - 3-32/64"
HSS52	1/2"	2-52/64" - 3-48/64"
HSS56	1/2"	3-4/64" - 4"
HSS60	1/2"	3-20/64" - 4-16/64"
HSS64	9-16"	3-36/64" - 4-32/64"
HSS72	9-16"	1-56/64" - 5"
HSS80	9-16"	2-32/64" - 5-32/64"
HSS104	9-16"	4-8/64" - 7"
HSS152	9-16"	7-8/64" - 10"

Miniature Worm Gear Clamps

Miniature all stainless construction with combination 1/4" hexagon and screwdriver slotted screw. Marine Grade SAE 300 series stainless band and housing. SAE 305 stainless screw. 5/16" band width. Available individually or in a box of 10



PART #	CLAMP SIZE	FITS HOSE MIN/MAX
WORM GEAR HOSE CLAMP		
MAH4	5/16"	14/64" - 40/64"
MAH6	5/16"	28/64" - 50/64"
MAH8	5/16"	32/64" - 58/64"
MAH10	5/16"	36/64" - 1-48/64"

Tubing & Hose Cutters

Features:

- Cuts hose and tubing to 2" O.D;
- P.E. up to 1-1/2" I.D.
- Stainless Steel replaceable blade

How to Order:

LHC95
LHC95RB (Replacement Blade)

